

INDOOR AMENITY LUMINAIRE

LED CIRCULUX

Circulux shown here with the optional
clear glass attachment

CIR/CG: suffix for order code



Tel: 01208 79524

Fax: 01208 72832

info@fitzlight.co.uk

www.fitzlight.co.uk

Fitzgerald^{FL}
Lighting your world

Fitzgerald Lighting (Cornwall) Limited, 38 Normandy Way, Bodmin, Cornwall PL31 1EX

LED CIRCULUX

INDOOR AMENITY LUMINAIRE

Fitzgerald^{FL}
www.fitzlight.co.uk

IP20

IP65

The LED Circulux is a bold range of recessed downlighters incorporating unrivalled optics that will enhance your project.

The Circulux product range is a lighting solution that can be used on a variety of applications.

Applications:

- Receptions
- Meeting Rooms
- Board Rooms
- Corridors & Walkways
- Toilets
- Auxillary Lighting

Product Specifications:

- White paint finish as standard
- Constant output driver with colour 840 as standard
- Highly specular anodised reflector supplied as standard

Occupancy and daylight sensor options available on this product



Optional Accessories: Mounting Bezel (/MB) must also be order to use these accessories



CIR/CG
Drop Clear
Glass



CIR/CGS
Drop Clear
Glass Spot



CIR/HR
Drop
Halo Ring



CIR/HO
Drop Halo
Ring Opal




CIR/65P
IP65
Sealed Bezel

Order Codes

LED Circulux	Lumens	Watts	Diameter	Height
CIR13/CO/840	1100	13	195	160
CIR23/CO/840	2000	23	195	160
CIR37/CO/840	3000	37	195	160

LED Circulux part code formula example:

Product Family	Watts	Gear Option	Optional Feature	Colour Temp	Emergency Option
CIR	23	DL	MB	840	RLS3



Polar Curve:
Photometric data is available online for dialux and relux.

Gear Options:

/AD: 1-10V Analogue dimming

/DL: Dali addressable dimming

Emergency Options:

/RLS3: 3hr remote sustained emergency

Optional Features:

/MB: Mounting bezel

Installation options:

Exposed T	YES
Plasterboard	YES
Metal Pan	YES
Surface	NO
Suspended	NO