

SURFACE MOUNTED LUMINAIRE

LED TANDEM STREAMLINE



Tel: 01208 79524

Fax: 01208 72832

info@fitzlight.co.uk

www.fitzlight.co.uk

Fitzgerald^{FL}
Lighting your world

Fitzgerald Lighting (Cornwall) Limited, 38 Normandy Way, Bodmin, Cornwall PL31 1EX

LED TANDEM STREAMLINE

SURFACE MOUNTED LUMINAIRE

Developed to meet the challenge of replacing 8 foot luminaires.

Older 8 foot luminaires are gradually becoming obsolete with the lamps and control gear being phased out.

The LED Tandem Streamline offers exceptional energy savings and reduces installation costs by using the same footprint.

Product Specifications:

- Manufactured from mild steel with white paint finish and containing an extruded aluminium chassis with a specially designed PMMA diffuser
- Constant output driver with colour 850 as standard

Optional Features:

/BK: Black paint finish


Colour Temperature Options:

/830: Colour 830

/840: Colour 840

Applications:

- Schools
- Offices
- Kitchens
- Workshops
- Corridors



Gear Options:

/AD: 1-10V Analogue dimming

/DL: Dali addressable dimming

Emergency Options:

/M3: 3hr maintained emergency

Installation options:

Exposed T	NO
Plasterboard	NO
Metal Pan	NO
Surface	YES
Suspended	YES

Occupancy and daylight sensor options available on this product



Sensor options are available on this product.

Are you still running old costly 8ft monsters?

Here at Fitzgerald Lighting we have developed an energy saving and easy to install solution using the LED Tandem Streamline.



Features of the Tandem Streamline

Similar dimensions to old 8ft T12 batten fittings

- no need for additional wiring/conduit
- no need for additional trunking lid
- no need to change chain suspension attachments

Exchange inefficient and costly T12 tubes for LED

- 50,000 hours
- large reduction in lamp costs and circuit watts
- similar/superior light output
- quality electronic drivers

Order Codes

Low Density Diffuser	Lumens	Watts	Length	Width	Height	Fix B	Fix C	Fix D
LSL44/8/CO/850	5444	44	2427	59	91	2200	1800	228
LSL88/8T/CO/850	10888	88	2427	59	91	2200	1800	228
Med Density Diffuser								
LSM44/8/CO/850	5444	44	2427	59	91	2200	1800	228
LSM88/8T/CO/850	10888	88	2427	59	91	2200	1800	228