



Glossary of terms

Colour if not white will be stated in the code of each product in the optional features section.

Colour:

SI	Silver/Grey
BZ	Antique Bronze
BR	Brass
BS	Brushed Steel
BK	Black
CH	Chrome
GY	Grey (RAL9006)
LG	Light Grey (RAL7035)
OW	Off White (RAL9010)

Gear Options:

AD	1-10v Analogue Dimming
SD	Retractive switch Dimming
DD	DSI Digital Dimming
DL	Dali Addressable Dimming
CO	Constant Output

Body Style: (nominal size)

2	2 foot
3	3 foot
4	4 foot
5	5 foot
6	6 foot
8	8 foot

2T	2 foot twin
3T	3 foot twin
4T	4 foot twin
5T	5 foot twin
6T	6 foot twin
8T	8 foot twin
A	A size body = 1200 x 300
B	B size body = 600 x 600
C	C size body = 1200 x 600
J	J size body = 300 x 300
K	K size body = 600 x 300
L	Large
M	Medium
S	Small

Emergency:

M3	3hr Maintained Emergency
NM3	3hr Non Maintained Emergency
RM3	Remote Maintained Emergency
LS3	LED 3hr Sustained Emergency
RLS3	LED 3hr Remote Sustained Emergency
M3T	3hr Maintained Self Test Emergency
NM3T	3hr Non Maintained Self Test Emergency

Optional Feature:

CIR	Shield style circles
------------	----------------------

LSQ	Shield style large squares
SSQ	Shield style small
LOGO	Shield style laser cut logo
SB4	Mounting brackets
54P	IP54 attachment
65P	IP65 attachment
40P	IP40 attachment
FTB	Fuse terminal block
SRB	Semi Recessed bezel
1.5SK	1.5m suspension kit
3SK	3m suspension kit
LEDNL	Integral 1W LED nightlight option
CMK	Corner mounting kit
START	Start of run
CONT	Continuation of run
END	End of run
HA	Halo effect
P	Prismatic diffuser
TPS	Tamper proof screws
PEC	Dusk to dawn sensing Photo-electric cell
MB	Mounting bezel
AH	Airhandling
UB	Unbranded (no FL logo)

Gel Colours:

GOW	Gel opaque white
GGR	Gel opaque green
GBL	Gel opaque Blue
GYE	Gel opaque Yellow
GRE	Gel opaque Red